


- 7** 7 Years
Product Warranty
- 2** 2 Years
On-Site Warranty
- 1000V**
Surge Protection

Easy fixing emergency driver



Leads Included



Recommended product

Trent III	↳ P245
Trent OnSite II	↳ P251
Avon 5	↳ P236
Niva III	↳ P201
Niva Go	↳ P206
Kennet III	↳ P213

General
Specification

Input Voltage	220-240Vac (BEM303/SST) 100-120Vac (BEM303-110/SST) 50/60Hz
Input Current (max)	18mA
Emergency Conversion Time	<1s
Emergency Operation Time	3h
Charging Time	24h
Ambient Temp	0°C to 50°C
Maximum Case Temp	75°C





Batten UEM 2 in 1

Dual-mode Standard & Self-test
3W emergency module for Kosnic LED batten luminaires

- To set the standard or self-test mode, press the push switch three times
- To set the duration test interval, press the push switch twice
- For maintained or non-maintained emergency lighting systems
- Automatic Self-test conforming to BS-EN-62034
- Designed for easy installation and battery replacement
- Internal LiFePO4 battery with improved lifespan
- With patented adaptive current control, this emergency module is suitable for LED load with a forward voltage between 30 to 300V

- STD**
ATS Dual test mode
- 26WK**
52WK Duration test interval
- 7**
YEAR Battery warranty
- Temp. Control**

Installation
Fault WarningStandard
EmergencySelf-test (ATS)
Emergency

LED Indicator

See page 60 for more information on the LED indicator reporting patterns

● ————— System Healthy	● ————— Battery Charging Fault
* — 1/2 s — Duration Test Pending	* - - - 1/4 s - - - Battery Duration Fault
* - - 1/4 s - - - Duration Test Running	* - - - 1/8 s - - - Lamp or Luminaire Fault
* - - - 1/8 s - - - Functional Test Running	
● ● Continuous On — On	
* * Flash - - - Off	

Order Code	Output Wattage (Max)	Input Voltage	Output Voltage	Battery	Battery Capacity	Output Current
BEM303/SST	3W	220-240Vac	30-300Vdc	LiFePO4	2000mAh	8-80mA

Low Input Voltage

Order Code	Output Wattage (Max)	Input Voltage	Output Voltage	Battery	Battery Capacity	Output Current
BEM303-110/SST	3W	100-120Vac	30-300Vdc	LiFePO4	2000mAh	8-80mA

Battery

Order Code	Type	Capacity	Voltage
BATS20LFP2	LiFePO4	2000mAh	6.4V

Patent

Order Code
BEM303/SST
BEM303-110/SST

